

Messprotokolle für EVE (Beispiel)

EVE (Empfänger)

Ü	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26
B	^{H/V}	x	x	x	^{H/V}	^{H/V}	^{H/V}	^{H/V}	x	^{H/V}	^{H/V}	x	x	x	^{H/V}	x	^{H/V}	x	x	^{H/V}	^{H/V}	^{H/V}	^{H/V}	x	^{H/V}	^{H/V}
S	1	x	1	0	x	1	x	x	0	0	0	x	1	x	x	1	0	x	1	x	x	x	0	1	x	0
Ü	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51	52
B	^{H/V}	x	^{H/V}	^{H/V}	^{H/V}	^{H/V}	x	x	^{H/V}	x	^{H/V}	^{H/V}	x	^{H/V}	^{H/V}	^{H/V}	^{H/V}	x	x	x	^{H/V}	x	^{H/V}	^{H/V}	^{H/V}	x
S	1	x	1	x	x	0	1	0	x	1	x	0	1	x	1	x	0	0	x	1	x	0	0	0	x	1

Ü = Übertragene Bits B = Basis (+) oder (X) S = Schlüsselbits

Bei allen Messungen mit einem „x“ muss EVE raten, welcher Wert richtig ist.

EVE (Sender)

Ü	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	
B	^{H/V}	x	x	x	^{H/V}	^{H/V}	^{H/V}	^{H/V}	x	^{H/V}	^{H/V}	x	x	x	^{H/V}	x	^{H/V}	x	x	^{H/V}	^{H/V}	^{H/V}	^{H/V}	x	^{H/V}	^{H/V}	
S	1	1	1	0	1	1	0	1	0	0	0	1	1	1	0	1	0	1	1	1	0	1	0	1	1	0	
Ü	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	50	51	52	
B	^{H/V}	x	^{H/V}	^{H/V}	^{H/V}	^{H/V}	x	x	^{H/V}	x	^{H/V}	^{H/V}	x	^{H/V}	^{H/V}	^{H/V}	^{H/V}	x	x	x	^{H/V}	x	^{H/V}	^{H/V}	^{H/V}	x	
S	1	0	1	1	0	0	1	0	0	1	1	0	1	1	1	0	0	0	1	1	0	0	0	0	0	1	1

Ü = Übertragene Bits B = Basis (+) oder (X) S = Schlüsselbits

Alle rot hinterlegten Felder sind geratene Bitwerte!